



FS-1135MFP

Black & White Multifunctional Printer

ECONOMICAL. ECOLOGICAL. ECOSYS TECHNOLOGY.

- Fast output speed of 37 pages per minute
- Standard print, copy, fax, and color scan
- Standard duplex and 300 sheet paper capacity
- USB host interface for convenient print-from and scan-to functionality
- LED illumination source for reduced energy consumption
- RAM-based Private Print capabilities
- ECOSYS® long life consumables reduce operating costs
- Kyocera ultra-reliable technology





FS-1135MFP



FS-1135MFP shown with standard configuration
19.4" W x 16.9" D x 17.6" H



FS-1135MFP shown with 2 optional (PF-120) paper drawers
19.4" W x 16.9" D x 25.4" H



Easy-to-replace toner container

KYOCERA Document Solutions America's objective is to manufacture superior products with a low Total Cost of Ownership (TCO) and minimize the impact on the environment. Kyocera's ECOSYS printers incorporate a patented long life drum which is separate from the toner container, eliminating the need to replace the drum when toner is depleted – and reducing landfill waste.

ECOSYS printers provide customers with a printing solution that incorporates long life consumables and one of the lowest costs per print. The operating costs of traditional cartridge-based printers can easily exceed many times the original purchase price during the life of the product. Evaluate your printer costs today.



Basic Specifications

Configuration	Black & White Multifunctional Printer - Standard Copy, Print, Fax, and Color Scan
Pages Per Minute	Letter: 37 ppm; Legal: 30 ppm; A4: 35 ppm; Duplex: 20 ppm (Letter)
Warm-up Time	20 Seconds or Less
First Copy / Print Out Time	6.9 Seconds / 7.0 Seconds
Resolution	1200 x 1200 dpi, 1800 x 600 dpi (Fast 1200 Mode), 600 x 600 dpi, 300 x 300 dpi
Memory (Standard / Maximum)	256 MB / 768 MB
Duplex	Standard Stackless
Electrical Requirements	120V, 60Hz, 10.0A or more; 220-240V, 50/60Hz, 6.0A
Dimensions / Weight	19.4" W x 16.9" D x 17.6" H / 40.0 lbs (standard configuration)
TEC	3,600 Wh/week
Maximum Monthly Duty Cycle	50,000 Pages Per Month

Paper Supply

Standard Paper Sources	Standard 250 Sheet Paper Drawer, 50 Sheet Multi Purpose Tray
Optional Paper Sources	Up to two (2) optional 250 Sheet Paper Drawers (PF-120) can be added
Paper Capacity	Standard: 300 Sheets; Maximum: 800 Sheets
Paper Size	4.1" x 5.8" - 8.5" x 14" via Drawers, 2.8" x 5.8" - 8.5" x 14" via MPT
Paper Weight	Drawers: 16 - 32 lb Bond (60 - 120gsm); MPT: 16 lb Bond - 120 lb Index (60 - 220gsm)
Input Materials	Bond Paper, Recycled Paper, Transparencies, Labels, Envelopes (MPT only)

Document Processor

Type / Capacity	Standard Reversing Automatic Document Processor / 50 Sheets (Letter)
Copy Scan Speed	35 ipm
Acceptable Originals / Weights	Letter, Legal, A4 / Simplex: 13 - 32 lb Bond (50 - 120gsm), Duplex 13 - 29 lb Bond (50 - 110gsm)

Duplex

Paper Size	Letter, Legal, A4
Paper Weight	16 - 28 lb Bond (60 - 105gsm)
Duplex Modes	1:2; 2:2; 2:1

Copy Specifications

Image Mode	Text, Photo, Text/Photo
Continuous Copy	Yes 1 - 999 / Auto Reset to 1
Additional Copy Features	Auto Magnification, Auto Paper Select, Auto Start, Auto Drawer Change, Priority Copy, Job Programs
Magnification / Zoom	Full Size, 7 Reduction, 5 Enlargement Preset Ratios, 25 - 400% in 1% step increments
Document Box	Job Box for RAM Based Private Print, Removable Memory for Print-From / Scan-To USB

Printer Specifications

Controller	PowerPC 440 / 667MHz
PDLs / Emulations	PRESCRIBE, PCL6 (5e, XL), KPDL3 (PS3), XPS, PDF 1.5, IBM ProPrinter X24E, Epson LQ-850, Diablo 630, Line Printer
Fonts	101 KPDL3, 93 PCL6, 8 Vista, 1 Bitmap, 45 Barcodes, 1 PDF 417
Windows OS Compatibility	Windows XP / 2003 / Vista / 2008 / 7
Mac OS Compatibility	Mac OS 10.x
UNIX OS Compatibility	Sun OS4.1x; Solaris 2.x; AIX; HP-UX (LPR)
Interfaces	Standard: 10/100BaseTX, Hi-Speed USB 2.0, USB Host Interface
Network Print and Supported Protocols	TCP/IP, NetWare, AppleTalk, NetBEUI, IPsec, HTTPS, LDAP over SSL, SNMPv3, POP over SSL/SMTP over SSL
Drivers	KX Driver, Mini Driver, PPD for Mac, PPD for UNIX
Utilities	PRESCRIBE, KMnet Admin, KMnet Viewer, Status Monitor, PDF Direct Print, Command Center

Scan Specifications

Scan Type	Color and Black & White Scanner
Scan Resolution	600dpi, 400dpi, 300dpi, 200dpi, 200 x 400dpi, 200 x 100dpi
Network Scan Speed	Mono: 300 dpi - 35 ipm Simplex; 18 ipm Duplex; 600 dpi - 20 ipm Simplex; 11 ipm Duplex Color: 300 dpi - 14 ipm Simplex; 8 ipm Duplex; 600 dpi - 7 ipm Simplex; 4 ipm Duplex
File Formats	TIFF, JPEG, XPS, PDF (Ver 1.4)
Connectivity / Supported Protocols	10/100BaseTX / TCP/IP; Hi-Speed USB 2.0
Scanning Functions	Scan to PC, Scan to e-mail, Scan to FTP, Scan to USB, WSD Scan
Driver	TWAIN Driver, WIA Driver

Fax Specifications

Fax Type Compatibility	ITU-T Group3
Data Compression	MH / MR / MMR / JBIG
Fax Transmission Selection	Text, Photo, Text/Photo
Fax Memory	3.5 MB
Transmission Speed / Modem	3 Seconds or less per page / 33.6 kbps
Fax Memory Capacity	256 Sheets or more
Network Fax Reception	Supports SMB/FTP/e-mail protocols
Fax Functions	Duplex Transmission/Reception, One Touch Dial (22 numbers), FAX/TEL Switching, Sequential Broadcast (up to 100 parties), Quick Dial (100 numbers), Fax Reports

USB Host Interface

Type	Supports direct printing and scanning from/to USB Drive
Supported File Types	Print: PDF, TIFF, XPS Scan: PDF (Ver 1.4), JPEG, TIFF, XPS

Optional Paper Drawers

Paper Capacity	250 Sheets
Maximum Drawers	Up to two (2) PF-120 drawers can be added
Paper Size	Letter, Legal, A4, A5R, B5, Folio, Oficio 2, 5.8" x 8.3" - 8.5" x 14"
Paper Weight	16 - 32 lb Bond (60 - 120gsm)
Dimensions / Weight	14.8" W x 15.6" D x 3.9" H / 7.7 lbs

Additional Options

Memory	Optional 256 MB, Optional 512 MB
--------	----------------------------------

Specifications and design are subject to change without notice.
For the latest on connectivity visit www.kyoceradocumentsolutions.com.
All trademarks are the property of their respective owners.

KYOCERA Document Solutions America, Inc.
Headquarters: 225 Sand Road, Fairfield, NJ 07004-0008, USA
© 2012 KYOCERA Document Solutions America, Inc.

IC# 855D400324

